



Package Dimensions:35x10x9

Package Weight:1150g



PRODUCT

BREEZE RIFLESCOPE

Compact

MODEL

3-12x44FFPIR

3-12x44FFP

3-12x44SFPIR

3-12x44SFP

RETICLE

FFP MOA

FFP MOA

SFP MOA

SFP MOA

SKU#

C30312

C30313

C30312S

C30313S

IDEAL APPLICATION



HUNTING


ALTERNATIVE APPLICATION



LONG RANGE



FFP



SFP

FEATURES

- Aerospace-grade T7075 aluminum tube
- Etched illuminated glass reticle
- IPX7 waterproof rating-One piece tube design-Nitrogen-filled for fog resistance
- 5 year warranty

SELF LOCKING TURRET

Its main feature is that it can prevent adjustment deviation due to accidental collision or touch during transportation, carrying or use through the locking mechanism, ensuring that the aiming point set by the shooter always remains unchanged

KEY FEATURES OF KECK GLASS RETICLE

Clear Vision: High-quality glass and coating technology ensure clear markings in all lighting conditions.Precise Scale: Laser-engraved for accuracy, allowing quick target adjustments.Durable: Impact-resistant and heat-resistant, suitable for harsh environments.Wide Application: Suitable for tactical shooting, sniper operations, long-range hunting, and competitive shooting, meeting the diverse needs of both military and civilian shooters.

ALL FEATURES



At 100 yards, after 1000 rounds of 7.62x51mm live fire, the deviation was less than 2 MOA with no noticeable shift in the aiming point. Despite the strong recoil, the lenses and internal optical components remained intact, with no damage or displacement, and the optical clarity and brightness were unaffected. The external protection and internal mounting systems showed no loosening or damage, ensuring long-term aiming stability.

Conclusion: The 7.62x51mm test confirms the excellent shock resistance of KECK scopes. Whether facing strong recoil or prolonged use, they consistently maintain precise aiming and superior optical performance, providing reliable tactical support.

SPECS

Magnification:	3-12x44
Scope Tube Diameter:	30mm
Lens Coating:	fully green multi coated
Reticle Type (Etched / Wire):	reticle
Ocular Lens Diameter:	31mm
Objective Lens Diameter:	44mm
Exterior Finish:	Matte Black
Mounting Length:	105mm
Objective/Field of View/ (100yds) :	35.1-8.7 feet(6.7°-1.675°)
Exit Pupil:	14.6mm - 3.6mm
Eye Relief:	3.54"- 3.35"(90mm-85mm)
Diopter Adjustment:	± 2.0
Adjustment Click Value:	1/10 MIL
Max. elevation adjustment range (MOA):	80MOA
Max. windage adjustment range (MOA):	80MOA
Parallax correction(yds):	10yds-∞
Length:	9.65", (245.0mm)