



Package Dimensions:35x10x9

Package Weight:1250g



PRODUCT	MODEL	RETICLE	SKU#
BREEZE RIFLESCOPE	4-16x44FFPIR	FFP MOA	C30416
Compact	4-16x44FFP	FFP MOA	C30417
	4-16x44SFPIR	SFP MOA	C30416S
	4-16x44SFP	SFP MOA	C30417S



**IDEAL APPLICATION**



HUNTING



LONG RANGE



**FEATURES**

Aerospace-grade T7075 aluminum tube  
Etched illuminated glass reticle  
IPX7 waterproof rating-One piece tube design-Nitrogen-filled for fog resistance  
5 year warranty

**SELF LOCKING TURRET**

Its main feature is that it can prevent adjustment deviation due to accidental collision or touch during transportation, carrying or use through the locking mechanism, ensuring that the aiming point set by the shooter always remains unchanged

**KEY FEATURES OF KECK GLASS RETICLE**

Clear Vision: High-quality glass and coating technology ensure clear markings in all lighting conditions.Precise Scale: Laser-engraved for accuracy, allowing quick target adjustments.Durable: Impact-resistant and heat-resistant, suitable for harsh environments.Wide Application: Suitable for tactical shooting, sniper operations, long-range hunting, and competitive shooting, meeting the diverse needs of both military and civilian shooters.

**ALL FEATURES**



At 100 yards, after 1000 rounds of 7.62x51mm live fire, the deviation was less than 2 MOA with no noticeable shift in the aiming point. Despite the strong recoil, the lenses and internal optical components remained intact, with no damage or displacement, and the optical clarity and brightness were unaffected. The external protection and internal mounting systems showed no loosening or damage, ensuring long-term aiming stability.

Conclusion: The 7.62x51mm test confirms the excellent shock resistance of KECK scopes. Whether facing strong recoil or prolonged use, they consistently maintain precise aiming and superior optical performance, providing reliable tactical support.

**SPECS**

Magnification:	4-16x
Scope Tube Diameter:	30mm
Lens Coating:	fully green multi coated
Reticle Type (Etched / Wire):	reticle
Ocular Lens Diameter:	31mm
Objective Lens Diameter:	44mm
Exterior Finish:	Matte Black
Mounting Length:	106mm
Objective/Field of View/ (100yds) :	26.2-6.55 feet (5°-1.25°)
Exit Pupil:	11mm - 2.75mm
Eye Relief:	3.54"- 3.35", (90mm-85mm)
Diopter Adjustment:	± 2.0
Adjustment Click Value:	1/10 MIL
Max. elevation adjustment range (MOA):	60MOA
Max. windage adjustment range (MOA):	60MOA
Parallax correction(yds):	10yds-∞
Length:	10.6", (269.5mm)