

Package Dimensions:35x10x9

Package Weight:885g



PRODUCT

PRECISION ED RIFLESCOPE

PRECISION RIFLESCOPE

MODEL

ED 1-6x24FFPIR

ED 1-6x24SFPIR

1-6x24FFPIR

1-6x24SFPIR

RETICLE

FFP MOA

SFP MOA

FFP MOA

SFP MOA

SKU#

ED30016

ED30016S


G30016

G30016S


IDEAL APPLICATION



SHORT RANGE



FFP



SFP

TOP FEATURES

ADVANCED FULLY MULTI-COATED

Aerospace-grade T7075 aluminum tube

Etched illuminated glass reticle

IPX7 waterproof rating-One

piece tube design-Nitrogen-filled for fog

resistance

5 year warranty

REAL TEST RESULTS



At 100 yards, after 1000 rounds of 7.62x51mm live fire, the deviation was less than 2 MOA with no noticeable shift in the aiming point. Despite the strong recoil, the lenses and internal optical components remained intact, with no damage or displacement, and the optical clarity and brightness were unaffected. The external protection and internal mounting systems showed no loosening or damage, ensuring long-term aiming stability.

Conclusion: The 7.62x51mm test confirms the excellent shock resistance of KECK scopes. Whether facing strong recoil or prolonged use, they consistently maintain precise aiming and superior optical performance, providing reliable tactical support.

KEY FEATURES OF KECK GLASS RETICLE

Clear Vision: High-quality glass and coating technology ensure clear markings in all lighting conditions.
Precise Scale: Laser-engraved for accuracy, allowing quick target adjustments.
Durable: Impact-resistant and heat-resistant, suitable for harsh environments.
Wide Application: Suitable for tactical shooting, sniper operations, long-range hunting, and competitive shooting, meeting the diverse needs of both military and civilian shooters.

SPECS

Model Number :	1-6X24
Scope Tube Diameter:	30mm
Lens Coating :	fully green multi coated
Reticle Type (Etched / Wire) :	reticle
Ocular Lens Diameter :	35mm
Objective Lens Diameter :	24mm
Exterior Finish:	Matte Black
Mounting Length :	140mm
Objective/Field of View/ (100yds) :	24°-4°
Exit Pupil:	9mm - 4mm
Eye Relief:	3.74"(95mm)
Diopter Adjustment:	±2.5
Adjustment Click Value :	1/2MOA
Max. elevation/windage adjustment range(MOA):	±100MOA
Parallax correction(yds):	100yds
Length:	242mm