

Package Dimensions:35x10x9

Package Weight:885g



PRODUCT

PRECISION ED RIFLESCOPE

Tube 34mm

PRECISION RIFLESCOPE

Tube 30mm

MODEL

ED 1-10x26FFPIR

ED 1-10x26SFPIR

1-10x24FFPIR

1-10x24SFPIR

RETICLE

FFP MOA

SFP MOA

FFP MOA

SFP MOA

SKU#

ED34110

ED34110S


G30110

G30110S


IDEAL APPLICATION



SHORT RANGE



FFP



SFP

FEATURES

Aerospace-grade T7075 aluminum tube

Etched illuminated glass reticle

IPX7 waterproof rating-One

piece tube design-Nitrogen-filled for fog

resistance

5 year warranty

KEY FEATURES OF KECK GLASS RETICLE

Clear Vision: High-quality glass and coating technology ensure clear

markings in all lighting conditions.Precise Scale: Laser-engraved for

accuracy, allowing quick target adjustments.Durable: Impact-resistant

and heat-resistant, suitable for harsh environments.Wide Application:

Suitable for tactical shooting, sniper operations, long-range hunting, and

competitive shooting, meeting the diverse needs of both military and

civilian shooters.

REAL TEST RESULTS



At 100 yards, after 1000 rounds of 7.62x51mm live fire, the deviation was less than 2 MOA with no noticeable shift in the aiming point. Despite the strong recoil, the lenses and internal optical components remained intact, with no damage or displacement, and the optical clarity and brightness were unaffected. The external protection and internal mounting systems showed no loosening or damage, ensuring long-term aiming stability.

Conclusion: The 7.62x51mm test confirms the excellent shock resistance of KECK scopes. Whether facing strong recoil or prolonged use, they consistently maintain precise aiming and superior optical performance, providing reliable tactical support.

SPECS

Model Number :	1-10X26
Scope Tube Diameter:	30mm/34mm
Lens Coating :	fully green multi coated
Reticle Type (Etched / Wire) :	reticle
Ocular Lens Diameter :	38mm
Objective Lens Diameter :	26mm
Exterior Finish:	Matte Black
Mounting Length :	140mm
Objective/Field of View/ (100yds) :	23°-2.3°
Exit Pupil:	8mm - 2.8mm
Eye Relief:	3.74"(95mm)
Diopter Adjustment:	±2.5
Adjustment Click Value :	1/2MOA
Max. elevation/windage adjustment range (MOA):	±100MOA
Parallax correction(yds):	100yds
Length:	259mm