



PRODUCT

PRECISION HD RIFLESCOPE

MODEL

2-12x50FFPIR

2-12x50FFP

PRECISION HD RIFLESCOPE

2-12x50SFPIR

2-12x50SFP

RETICLE

FFP MIL

SFP MIL

SKU#

G30212

G30213

G30212S

G30213S

IDEAL APPLICATION




HUNTING


ALTERNATIVE APPLICATION



LONG RANGE



FFP



SFP

FEATURES

Aerospace-grade T7075 aluminum tube
Etched illuminated glass reticle
IPX7 waterproof rating-One piece tube design-Nitrogen-filled for fog resistance
5 year warranty

PRECISION ZERO STOP

Advanced adjustment function is used to help the shooter quickly and accurately return to the initial zero position. The core function of this system is to easily return the adjustment knob to the original zero position after the shooter makes an elevation adjustment.

KEY FEATURES OF KECK GLASS RETICLE

Clear Vision: High-quality glass and coating technology ensure clear markings in all lighting conditions.Precise Scale: Laser-engraved for accuracy, allowing quick target adjustments.Durable: Impact-resistant and heat-resistant, suitable for harsh environments.Wide Application: Suitable for tactical shooting, sniper operations, long-range hunting, and competitive shooting, meeting the diverse needs of both military and civilian shooters.

REAL TEST RESULTS



At 100 yards, after 2500 rounds of 7.62x51mm live fire, the deviation was less than 1.5 MOA with no noticeable shift in the aiming point. Despite the strong recoil, the lenses and internal optical components remained intact, with no damage or displacement, and the optical clarity and brightness were unaffected. The external protection and internal mounting systems showed no loosening or damage, ensuring long-term aiming stability.

Conclusion: The 7.62x51mm test confirms the excellent shock resistance of KECK scopes. Whether facing strong recoil or prolonged use, they consistently maintain precise aiming and superior optical performance, providing reliable tactical support.

SPECS

Magnification:	2-12x
Scope Tube Diameter:	30mm
Lens Coating:	fully green multi coated
Reticle Type (Etched / Wire):	reticle
Ocular Lens Diameter:	35mm
Objective Lens Diameter:	50mm
Exterior Finish:	Matte Black
Mounting Length:	140mm
Objective/Field of View/ (100yds) :	58.3-9.7 feet (10°-1.66°)
Exit Pupil:	10mm - 3.6mm
Eye Relief:	3.78"- 3.74",(96mm-95mm)
Diopter Adjustment:	± 2.0
Adjustment Click Value:	1/10 MIL
Max. elevation adjustment range (MOA):	±50MOA
Max. windage adjustment range (MOA):	±40MOA
Parallax correction(yds):	10yds-∞
Length:	12.5", (318.0mm)