





PRODUCT PRECISION HD RIFLESCOPE

PRECISION HD RIFLESCOPE

IDEAL APPLICATION



HUNTING

FEATURES

Aerospace-grade T7075 aluminum tube Etched illuminated glass reticle IPX7 waterproof rating-One piece tube design-Nitrogen-filled for fog resistance 5 year warranty

REAL TEST RESULTS



At 100 yards, after 2500 rounds of 7.62x51mm live fire, the deviation was less than 1.5 MOA with no noticeable shift in the aiming point. Despite the strong recoil, the lenses and internal optical components remained intact, with no damage or displacement, and the optical clarity and brightness were unaffected. The external protection and internal mounting systems showed no loosening or damage, ensuring long-term aiming stability. Conclusion: The 7.62x51mm test confirms the excellent shock resistance of KECK scopes. Whether facing strong recoil or prolonged use, they consistently maintain precise aiming and superior optical performance, providing reliable tactical support.

3-15x50SFPIR 3-15x50SFP

MODEL

3-15x50FFPIR 3-15x50FFP



LONG RANGE

PRECISION ZERO STOP

Advanced adjustment function is used to help the shooter quickly and accurately return to the initial zero position. The core function of this system is to easily return the adjustment knob to the original zero position after the shooter makes an elevation adjustment.

RETICLE	SKL	J#
FFP MIL	G30315	
	G30	316
SFP MIL	G30	315S
	G30	316S
Management of the second secon		
FFP	SFP	

KEY FEATURES OF KECK GLASS RETICLE

Clear Vision: High-quality glass and coating technology ensure clear markings in all lighting conditions. Precise Scale: Laserengraved for accuracy, allowing quick target adjustments.Durable: Impact-resistant and heat-resistant, suitable for harsh environments.Wide Application: Suitable for tactical shooting, sniper operations, long-range hunting, and competitive shooting, meeting the diverse needs of both military and civilian shooters.

SPECS

Magnification:	3-15x	
Scope Tube Diameter:	30mm	
Lens Coating:	fully green multi coated	
Reticle Type (Etched / Wire):	reticle	
Ocular Lens Diameter:	35mm	
Objective Lens Diameter:	50mm	
Exterior Finish:	Matte Black	
Mounting Length:	142mm	
Objective/Field of View/ (100yds) :	39.3-7.8 feet (7.5°-1.5°)	
Exit Pupil:	8.8mm - 2.8mm	
Eye Relief:	3.78"- 3.74",(96mm-95mm)	
Diopter Adjustment:	±2.0	
Adjustment Click Value:	1/4 MOA	
Max. elevation adjustment range (MOA):	100MOA	
Max. windage adjustment range (MOA):	80MOA	
Parallax correction(yds):	10yds-∞	
Length:	13.5", (343.0mm)	