

Package Dimensions:43x9.8x13.2 Package Weight:1300g



PRODUCT	MODEL	RETICLE	SKU#
PRECISION RIFLESCOPE	4-16x50FFPIR	FFP MIL	G30416
	4-16x50FFP		G30417
PRECISION RIFLESCOPE	4-16x44FFPIR	FFP MIL	G30416A
	4-16x44FFP		G30417
PRECISION RIFLESCOPE	4-16x50SFPIR	SFP MIL	G30416S
	4-16x50SFP		G30417S
PRECISION RIFLESCOPE	4-16x44SFPIR	SFP MIL	G30416AS
	4-16x44SFP		G30417AS

IDEAL APPLICATION

KECK OPTICS

CREATE VALUE FOR USERS



FEATURES

Aerospace-grade T7075 aluminum tube Etched illuminated glass reticle IPX7 waterproof rating-One piece tube design-Nitrogen-filled for fog resistance 5 year warranty

HUNTING

ALL FEATURES



At 100 yards, after 2500 rounds of 7.62x51mm live fire, the deviation was less than 1.5 MOA with no noticeable shift in the aiming point. Despite the strong recoil, the lenses and internal optical components remained intact, with no damage or displacement, and the optical clarity and brightness were unaffected. The external protection and internal mounting systems showed no loosening or damage, ensuring long-term aiming stability. Conclusion: The 7.62x51mm test confirms the excellent shock resistance of KECK scopes. Whether facing strong recoil or prolonged use, they consistently maintain precise aiming and superior optical performance, providing reliable tactical support.

ALTERNATIVE APPLICATION



LONG RANGE

PRECISION ZERO STOP

Advanced adjustment function is used to help the shooter quickly and accurately return to the initial zero position. The core function of this system is to easily return the adjustment knob to the original zero position after the shooter makes an elevation adjustment.



KEY FEATURES OF KECK GLASS RETICLE

Clear Vision: High-quality glass and coating technology ensure clear markings in all lighting conditions.Precise Scale: Laserengraved for accuracy, allowing quick target adjustments.Durable: Impact-resistant and heat-resistant, suitable for harsh environments.Wide Application: Suitable for tactical shooting, sniper operations, long-range hunting, and competitive shooting, meeting the diverse needs of both military and civilian shooters.

S	P	E	С	S

Magnification:	4-16x	
Scope Tube Diameter:	30mm	
Lens Coating:	fully green multi coated	
Reticle Type (Etched / Wire):	reticle	
Ocular Lens Diameter:	35mm	
Objective Lens Diameter:	44mm	
Exterior Finish:	Matte Black	
Mounting Length:	150mm	
Objective/Field of View/ (100yds) :	24.6-6.3feet (4.7°-1.2°)	
Exit Pupil:	11mm - 2.75mm	
Eye Relief:	4.13"- 3.93"(105mm-100mm)	
Diopter Adjustment:	±2.0	
Adjustment Click Value:	1/10 MIL	
Max. elevation adjustment range (MOA):	80MOA	
Max. windage adjustment range (MOA):	60MOA	
Parallax correction(yds):	10yds-∞	
Length:	14.0", (356.0mm)	