

Package Dimensions:43x9.8x13.2

Package Weight:1500g



| PRODUCT | MODEL | RETICLE | SKU# |
|--------------------------------------|----------------------------|---------|--------------------|
| PRECISION HD RIFLESCOPE Tube 34mm | 5-25x56FFPIR 5-25x56FFP | FFP MIL | G34525 G34526 |
| PRECISION HD RIFLESCOPE Tube 30mm | 5-25x50FFPIR 5-25x50FFP | FFP MIL | G30525 G30526 |
| PRECISION HD RIFLESCOPE Tube 34mm | 5-25x56SFPIR 5-25x56SFP | SFP MIL | G34525S G34526S |
| PRECISION HD RIFLESCOPE Tube 30mm | 5-25x50SFPIR 5-25x50SFP | SFP MIL | G30525S G30526S |

IDEAL APPLICATION




HUNTING


ALTERNATIVE APPLICATION



LONG RANGE



FFP



SFP

FEATURES

Aerospace-grade T7075 aluminum tube
 Etched illuminated glass reticle
 IPX7 waterproof rating-One piece tube design-Nitrogen-filled for fog resistance
 5 year warranty

PRECISION ZERO STOP

Advanced adjustment function is used to help the shooter quickly and accurately return to the initial zero position. The core function of this system is to easily return the adjustment knob to the original zero position after the shooter makes an elevation adjustment.

KEY FEATURES OF KECK GLASS RETICLE

Clear Vision: High-quality glass and coating technology ensure clear markings in all lighting conditions. Precise Scale: Laser-engraved for accuracy, allowing quick target adjustments. Durable: Impact-resistant and heat-resistant, suitable for harsh environments. Wide Application: Suitable for tactical shooting, sniper operations, long-range hunting, and competitive shooting, meeting the diverse needs of both military and civilian shooters.

REAL TEST RESULTS



At 100 yards, after 2500 rounds of 7.62x51mm live fire, the deviation was less than 1.5 MOA with no noticeable shift in the aiming point. Despite the strong recoil, the lenses and internal optical components remained intact, with no damage or displacement, and the optical clarity and brightness were unaffected. The external protection and internal mounting systems showed no loosening or damage, ensuring long-term aiming stability. Conclusion: The 7.62x51mm test confirms the excellent shock resistance of KECK scopes. Whether facing strong recoil or prolonged use, they consistently maintain precise aiming and superior optical performance, providing reliable tactical support.

SPECS

| | |
|--|----------------------------|
| Magnification: | 5-25x56 |
| Scope Tube Diameter: | 30mm/34mm |
| Lens Coating: | fully green multi coated |
| Reticle Type (Etched / Wire): | reticle |
| Ocular Lens Diameter: | 35mm |
| Objective Lens Diameter: | 50mm |
| Exterior Finish: | Matte Black |
| Mounting Length: | 152mm |
| Objective/Field of View/ (100yds) : | 23-4.6feet (4.4°-0.88°) |
| Exit Pupil: | 7mm - 2mm |
| Eye Relief: | 3.78" - 3.74", (96mm-95mm) |
| Diopter Adjustment: | ±2.0 |
| Adjustment Click Value: | 1/4 MOA |
| Max. elevation adjustment range (MOA): | 120MOA |
| Max. windage adjustment range (MOA): | 80MOA |
| Parallax correction(yds): | 10yds-∞ |
| Length: | 13.7", (347mm) |