



PRODUCT

PRECISION HD RIFLESCOPE
Tube 34mm
PRECISION HD RIFLESCOPE
Tube 34mm

MODEL

7-42x56FFPIR
7-42x56FFP
7-42x56SFPIR
7-42x56SFP

RETICLE

FFP MIL
SFP MIL

SKU#

G34742
G34743
G34742S
G34743S

IDEAL APPLICATION


ALTERNATIVE APPLICATION




HUNTING



LONG RANGE



FFP



SFP

FEATURES

Aerospace-grade T7075 aluminum tube
Etched illuminated glass reticle
IPX7 waterproof rating-One piece tube design-Nitrogen-filled for fog resistance
5 year warranty

PRECISION ZERO STOP

Advanced adjustment function is used to help the shooter quickly and accurately return to the initial zero position. The core function of this system is to easily return the adjustment knob to the original zero position after the shooter makes an elevation adjustment.

KEY FEATURES OF KECK GLASS RETICLE

Clear Vision: High-quality glass and coating technology ensure clear markings in all lighting conditions.Precise Scale: Laser-engraved for accuracy, allowing quick target adjustments.Durable: Impact-resistant and heat-resistant, suitable for harsh environments.Wide Application: Suitable for tactical shooting, sniper operations, long-range hunting, and competitive shooting, meeting the diverse needs of both military and civilian shooters.

REAL TEST RESULTS



At 100 yards, after 2500 rounds of 7.62x51mm live fire, the deviation was less than 1.5 MOA with no noticeable shift in the aiming point. Despite the strong recoil, the lenses and internal optical components remained intact, with no damage or displacement, and the optical clarity and brightness were unaffected. The external protection and internal mounting systems showed no loosening or damage, ensuring long-term aiming stability.
Conclusion: The 7.62x51mm test confirms the excellent shock resistance of KECK scopes. Whether facing strong recoil or prolonged use, they consistently maintain precise aiming and superior optical performance, providing reliable tactical support.

SPECS

Magnification:	7-42x56
Scope Tube Diameter:	34mm
Lens Coating:	fully green multi coated
Reticle Type (Etched / Wire):	reticle
Ocular Lens Diameter:	35mm
Objective Lens Diameter:	56mm
Exterior Finish:	Matte Black
Mounting Length:	200mm
Objective/Field of View/ (100yds) :	3.43°-0.57°
Exit Pupil:	8mm - 1.33mm
Eye Relief:	3.74", (95mm)
Diopter Adjustment:	±2.5
Adjustment Click Value:	1/4MOA
Max. elevation adjustment range (MOA):	±40MOA
Max. windage adjustment range (MOA):	±40MOA
Parallax correction(yds):	10yds-∞
Length:	402mm